



FICHA TÉCNICA

SAE 100 R15

CÓDIGO	DIÁMETRO INTERNO		DIÁMETRO EXTERNO	PRESIÓN MÁXIMA DE TRABAJO		PRESIÓN MÍNIMA DE RUPTURA		ROLLO		PESO	
CODE	INTERNAL DIAMETER		EXTERNAL DIAMETER	MAXIMUM WORKING PRESSURE		BURST PRESSURE		ROLL		WEIGHT	
	IN	MM	MM	PSI	BAR	PSI	BAR	MTS	PIE	KG/MTS	LB/PIE
R15-12	3/4	19,00	36.1	6.100	420,60	24.400	1.682	30	131,20	1,62	1,12
R15-16	1	25,40	42.9	6.100	420,60	24.400	1.682	30	131,20	2,18	1,51
R15-20	1 1/4	31,80	51.5	6.100	420,60	24.400	1.682	30	131,20	3,58	2,48
R15-24	1 1/2	38,10	59.6	6.100	420,60	24.400	1.682	30	131,20	4,50	3,12
R15-32	2	50,80	70,2	6.100	420,60	24.400	1.682	20	65,60	5,70	3,95



Aplicación:

Transferencia de fluidos hidráulicos a extrema presión y de altos picos. Sector petrolero, construcción, agricultura, industrias y automotriz



Ventajas:

Excede la norma. Diseñada para resistir picos de presión



Tubo:

Mezcla de goma sintética, resistente al aceite y combustible



Refuerzo:

Seis espirales de acero, altamente resistentes



Cubierta:

Mezcla de goma sintética, resistente al aceite, abrasión e intemperie



Color de Cubierta:

Negro, con una franja de color rojo



Marcado:

PROFIX +PIR (R15) XX" ~ XX MM I.D. SAE 100R15 EN 856 R15 MSHA APPROVED ISO 1307 (MAX. W.P. XXXX PSI ~ XXXX BAR) -40°C +121°C +15 +PIR



Rango de Temperatura:

Desde -40°C hasta +121°C.



Application:

Transfer of hydraulic fluids to extreme pressure and high peaks. Oil, construction, agriculture, industry and automotive sectors



Advantage:

Exceeds the norm. Designed to withstand pressure peaks



Tube:

Mixture of synthetic rubber, oil and fuel resistant



Reinforcement:

Six steel spirals, highly resistant



Cover:

Synthetic rubber mixture, resistant to oil, abrasion and weather



Cover Color:

Black with a red stripe



Branding:

PROFIX +PIR (R15) XX" ~ XX MM I.D. SAE 100R15 EN 856 R15 MSHA APPROVED ISO 1307 (MAX. W.P. XXXX PSI ~ XXXX BAR) -40°C +121°C +15 +PIR



Temperature range:

-40°C to +121°C.

